



NOTES:

- 1) ALL DIMENSIONS ARE IN mm WITH CONVERSION FOR (INCHES).
- 2) CMA ACTUATORS CAN BE SELECTED WITH EITHER METRIC OR IMPERIAL SIZES FOR MOUNTING, SHAFT AND CONDUIT ENTRY. THESE ARE NOT SIMPLE CONVERSIONS BUT DIFFERENT DIMENSIONS.

DIMENSIONS WITH ' * 'INDICATE COVER REMOVAL ALLOWANCE.

THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR ON TO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATE TOLERANCES, THREAD ENGAGEMENT, SCREW TORQUES, SIZES, MATERIALS & FORM TOLERANCES.

UNIT WEIGHT - 25.4 lbs (11.5 kg)

TOLERANCES DIMENSIONS IN MILLIMETERS JNLESS OTHERWISE SPECIFIED ±.5mm .XX = ±.1mm ANGULAR ±1° E: 1:2			rotork	CMA INSTALLATION DRAWING		
V	PROD. DV.	PROD. ENG.	Process Controls MILWAUKEE, WISCONSIN, USA	FOR:	FOR: CML-750	
5/15	DATE:	DATE: 09/20/12	This print is the property of Rotork Process Controls and is loaned in confidence subject to return. All rights to design or invention are reserved.	96	D	047526