



NOTES:

- 1) ALL DIMENSIONS ARE IN mm WITH CONVERSION FOR (INCHES).
- 2) CMA ACTUATORS CAN BE SELECTED WITH EITHER METRIC OR IMPERIAL SIZES FOR MOUNTING, SHAFT AND CONDUIT ENTRY. THESE ARE NOT SIMPLE CONVERSIONS BUT DIFFERENT DIMENSIONS.

DIMENSIONS WITH ' \* ' INDICATE COVER REMOVAL ALLOWANCE.

THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR ON TO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATE TOLERANCES, THREAD ENGAGEMENT, SCREW TORQUES, SIZES, MATERIALS & FORM TOLERANCES.

UNIT WEIGHT - 30.3 lbs (13.7 Kg)

<b>TOLERANCES</b> DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED X = ±.5mm XX = ±.1mm ANGULAR ±1°			 MILWAUKEE, WISCONSIN, USA	TITLE: CMA INSTALLATION DRAWING
SCALE: 1:2	PROD. BY: RLY	PROD. ENG: RLY		FOR: CML-750 LONG COVER
DRAWN: RLY	DATE: 5/27/15	DATE: 12/13/13	This print is the property of Rotork Process Controls and is loaned in confidence subject to return. All rights to design or invention are reserved.	96 D 048322