

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170120-E303346  
**Report Reference** E303346-20040521  
**Issue Date** 2017-JANUARY-20

**Issued to:** ROTORK INSTRUMENTS ITALY SRL  
VIA PORTICO 17  
24050 ORIO AL SERIO BG ITALY

**This is to certify that  
representative samples of**

TELEMETERING EQUIPMENT FOR USE IN HAZARDOUS  
LOCATIONS

See addendum for models.

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** See addendum for standards.

**Additional Information:** See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170120-E303346  
**Report Reference** E303346-20040521  
**Issue Date** 2017-JANUARY-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Rotary Limit Switches, Models CA or CS followed by alphanumeric character; followed by 10, 13, 14, 16, C1, C3, C4, C8, N1, N2 or N3; followed by 1, 2, 3 or 4; followed by 0; followed by additional alphanumeric characters, followed by E and followed by LT or any alphanumeric character; for use in Class I, Division 2, Groups A, B, C and D, Class II, Division 2; Groups F and G Hazardous Locations.

Rotary Limit Switches, Models SF, SB or SS; followed by C1, C3, C4, C8, N1, N2 or N3; followed by 0, 1, 2, 3 or 4; followed by 0 or any alphanumeric character; followed by alphanumeric character; followed by 1, 2, 8 or any alphanumeric character; followed by alphanumeric character; followed by alphanumeric character; followed by alphanumeric character; followed by alphanumeric character; followed by 3, 6 or 7; followed by alphanumeric character; followed by alphanumeric character; followed by alphanumeric character for use in Class I, Division 2, Groups A, B, C and D, Class II, Division 2; Groups F and G Hazardous Locations

**Standards for Safety:**

ANSI/ISA 12.12.01-2013, Non-incendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations,


UL 508, Industrial control equipment

UL 50, Enclosures for Electrical Equipment

UL 840, Insulation Coordination Including Clearances and Creepage Distances for Electrical Equipment  
C22.2 No. 213-M1987, Non-incendive Electrical Equipment for Use in Class I, Division 2 Hazardous Locations

CSA C22.2 No. 14-13, Industrial Control Equipment

CAN/CSA C22.2 No. 157-92, Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

