



 Oil filler/drain plug

DOC1227-01

Actuator size	Dimension ins/mm						B	C	D	E	F
	40	60	A spring rating psi			125					
325 10	58.6/1488	59.6/1514	62.6/1590	64.6/1641	66.6/1692	69.6/1768	1/2"NPT	8.0/203	16.9/429	26.8/681	10.8/274
325 12	60.6/1539	63.6/1615	67.6/1717	69.6/1768	71.6/1819	73.6/1869	1/2"NPT	8.0/203	16.9/429	26.8/681	13.0/330
325 14	63.7/1618	67.7/1720	72.7/1847	73.7/1872	71.7/1822	76.7/1948	1/2"NPT	8.0/203	17.2/437	26.9/683	15.0/381
325 17	70.7/1796	75.7/1923	74.7/1897	79.7/2024	87.7/2228	87.7/2228	3/4"NPT	9.5/241	16.9/429	29.9/759	18.5/470
325-19	74.7/1897	74.7/1897	79.7/2024	87.7/2228	87.7/2228	---	3/4"NPT	9.5/241	16.9/429	29.9/759	20.8/528

Actuator size	Weights lbs/kg						Swept Volume US gal/liters
	40	60	spring rating psi			125	
325 10	397/180	409/185	420/190	428/194	441/200	455/206	2.29/8.69
325 12	452/205	463/210	484/220	498/225	511/232	526/239	3.30/12.52
325 14	513/233	535/243	577/262	590/268	595/270	703/319	4.50/17.04
325 17	852/296	681/309	875/397	900/408	943/429	988/449	6.60/24.98
325-19	784/356	806/366	831/377	871/395	914/415	---	8.73/33.06